

# LIQUID FIRE EXTINGUISHING ANTI-EXPLOSIVE DEICING & ENVIRONMENT REMEDIAL AGENTS CATALOGUE



**FIRESTOPPER®**  
Industrial - Commercial  
Government



## **FIRESTOPPER**

**THE WORLD'S FIRST MULTI FACETED  
"GREEN" SAFETY PRODUCTS LINE**

- AB40002 FFC • XL FFC • XL "PLUS" FFC • ENVIROSAFE® EBC
- ENVIROSAFE® ICESTOPPER™ • FIRESTOPPER® EXP

# AB40002 FFC

## An All Purpose Fire Fighting Catalyst Foam Concentrate Specially Designed for Professional Fire Fighters & Municipalities



The FFC, is a proprietary Trade Secret Technology and formulations, within the meaning of the Uniform Trade Secret Act ("UTSA") Cal. Civ. Code Sec. 3426, Common law, Business and Profession §17200 and all other applicable statutes.

### ENVIRONMENTAL & TOXICOLOGY TESTING

AB 40002 (FFC) was independently tested and found to be non-hazardous to fish. The mixture is not an eye or skin irritant and is non-toxic when tested according to the FHSA protocols. It is judged to pose no chronic health hazard. Under European standards (OECD 301 part B), FFC's meet "green" qualification. The FFCs require no special labeling or chronic health hazard warning statements and comply with FHSA regulations, 16 CFR 1500 and California Proposition 65.

**LIMITED WARRANTY**  
10-YEAR WHEN STORED WITHIN THE RECOMMENDED TEMPERATURE WHILE IN THE UNOPENED OR UNDAMAGED FACTORY SEALED ORIGINAL CONTAINER

### DESCRIPTION

**Technology:** Fire Fighting Catalyst (FFC) A High Kinetic Catalytic Foaming agent  
**Concentrate 6%**  
**Usable: 1-100% as Needed**  
**Training: 0.5%**

**Approvals & Listings:**  

- EN1568-3
- ICAO-B
- EN3-6
- UL (Completion IN 2014)

**UK MoD:**  

- 42-40 & 42-42 Milieukeur Certificate
- NPB 155-90 (Russian Fire Standard)

**Fire Class Effective:** ABCDK (Intl: ABCDF)  
**Subclass Effective:** Alcohols - Esters  

- Ethers
- Carbon Composites
- Rubber
- Plastics
- Magnesium etc.

**▲ Class A Structure Fires:**  

- Total prevention of thermal inversion phenomenon
- Fast knockdown
- Great retardant reliability no re-ignition

**▲ Class B K/F-ALL Hydrocarbon Fuels (Polar, Non Polar, Fats & Vegetable Oils) Great Cooling Effect No Emulsification of Fuels**

**▲ Class C/E-Effective On:** Transformer Fires; Pass Portable System "C"/E Testing @ 35kv  
**▲ Class D Effective On:** Magnesium, Aluminum, Titanium (Not Tested on Sodium & Lithium)

**Wildland Fire App.**  

- Air Drop
- Land Based
- Structure Pretreatment

- Fire Brakes
- Batch Mixable
- No Special Equipment Necessary
- Compatible with Other Products

**Additional Advantages**  

- Great Temperature Reduction (1800°F to 135°F < 40 sec.)

**Effective on Marine Fires (Adhere to surface such as fiberglass, etc.)**  

- Cold Environment Resistant: -4°F (-20°C)

**Storage & Handling**  

- Keep in original factory sealed container or poly tanks
- Avoid contamination of product to prevent biodegradation

**Storage: -4°F to 90°F (-20°C to 32°C)**  

- Do Not Store in Aluminum Container
- Do Not Mix with Hypocrite
- Do Not Use Zinc Metals, Copper or Brass Dip Tubes

**Packaging:** • 55-gal Poly Drums (208-L) Fill wt.: 540-lbs (245-kg) • 5-gal Carboy (20-L) Fill wt.: 49-lbs  

- Bulk Packaging (By Request)

**Technical Specifications**  
 pH @ 25°C: 7.2-7.9  
 S.G. @ 25°C: 1.100-1.200

# XL FFC

## A High Performance All Fire Surfaces Class Effective Concentrate



DESCRIPTION	
Technology: Fire Fighting Catalyst (FFC) A High Kinetic Catalytic Foaming agent	Concentrate 3% & 6% Usable: 1-100% as Needed Training: 0.5%
Approvals & Listings: • EN1568-3 @ 3% 6% (I-A; II-A) • ICAO-B @ 6%	US Approvals to be completed in 2014 at UL Testing Facilities
Fire Class Effective: ABCDK (Intl: ABCDF) Subclass Effective: Alcohols - Esters	<ul style="list-style-type: none"> <li>• Ethers • Carbon Composites</li> <li>• Rubber • Plastics</li> <li>• Magnesium etc.</li> </ul>
<ul style="list-style-type: none"> <li>▲ Class A Structure Fires:</li> <li>• Total prevention of thermal inversion phenomenon</li> <li>• Fast knockdown</li> <li>• Great retardant reliability no re-ignition</li> </ul>	<ul style="list-style-type: none"> <li>▲ Class B K/F-ALL Hydrocarbon Fuels (Polar, Non Polar, Fats &amp; Vegetable Oils) Great Cooling Effect No Emulsification of Fuels</li> </ul>
▲ Class C/E-Effective On: Transformer Fires; Pass Portable System "C"/E	▲ Class D Effective On: Magnesium, Aluminum, Titanium (Not Tested on Sodium & Lithium)
Wildland Fire App. • Air Drop • Land Based • Structure Pretreatment	<ul style="list-style-type: none"> <li>• Fire Brakes • Batch Mixable</li> <li>• No Special Equipment Necessary</li> <li>• Compatible with Other Products</li> </ul>
Additional Advantages • Great Temperature Reduction (1800°F to 135°F < 40 sec.)	Effective on Marine Fires (Adhere to surface such as fiberglass, etc.) • Cold Environment Resistant: -13°F (-25°C)
Storage & Handling • Keep in original factory sealed container or poly tanks • Avoid contamination of product to prevent biodegradation	Storage: -4°F to 100°F (-20°C to 37°C) • Do Not Store in Aluminum Container • Do Not Mix with Hypocrite • Do Not Use Zinc Metals, Copper or Brass Dip Tubes
Packaging: • 55-gal Poly Drums (208-L) Fill wt.: 540-lbs (245-kg) • 5-gal Carboy (20-L) Fill wt.: 49-lbs	• Bulk Packaging (By Request) 275-gal EU: 1000-L 330-gal
Technical Specifications	pH @ 25°C: 7.2-7.9 S.G. @ 25°C: 1.100-1.200



The FFC, is a proprietary Trade Secret Technology and formulations, within the meaning of the Uniform Trade Secret Act ("UTSA") Cal. Civ. Code Sec. 3426, Common law, Business and Profession §17200 and all other applicable statutes.

### ENVIRONMENTAL & TOXICOLOGY TESTING

FFCs' are independently tested and found to be non-hazardous to fish or any other life forms. The mixture is not an eye or skin irritant and is non-toxic when tested according to the FHSA protocols. It is judged to pose no chronic health hazard. Under European standards OECD 306, and 117 Method 2004, ISO 14669 (1999), ISO 5667-16 (1998), and ISO 10253 2006; (OSPAR/HOCNF) Part B, the FFCs meet "Green" 1 qualifying requirements. The FFCs need no special labeling or chronic health hazard warning statements and are in compliance with FHSA regulations, 16 CFR 1500 and California Proposition 65.

**LIMITED WARRANTY**  
10-YEAR WHEN STORED WITHIN THE RECOMMENDED TEMPERATURE WHILE IN THE UNOPENED OR UNDAMAGED FACTORY SEALED ORIGINAL CONTAINER

# XL "PLUS" FFC

## Designed for High Risk Life & Property Protection



The FFC, is a proprietary Trade Secret Technology and formulations, within the meaning of the Uniform Trade Secret Act ("UTSA") Cal. Civ. Code Sec. 3426, Common law, Business and Profession §17200 and all other applicable statutes.

### ENVIRONMENTAL & TOXICOLOGY TESTING

FFCs' are independently tested and found to be non-hazardous to fish or any other life forms. The mixture is not an eye or skin irritant and is non-toxic when tested according to the FHSa protocols. It is judged to pose no chronic health hazard. Under European standards OECD 306, and 117 Method 2004, ISO 14669 (1999), ISO 5667-16 (1998), and ISO 10253 2006; (OSPAR/HOCNF) Part B, the FFCs meet "Green" 1 qualifying requirements. The FFCs need no special labeling or chronic health hazard warning statements and are in compliance with FHSa regulations, 16 CFR 1500 and California Proposition 65.

**LIMITED WARRANTY**  
**10-YEAR WHEN STORED WITHIN THE RECOMMENDED TEMPERATURE WHILE IN THE UNOPENED OR UNDAMAGED FACTORY SEALED ORIGINAL CONTAINER**

### DESCRIPTION

**Technology:** Fire Fighting Catalyst (FFC) A High Kinetic Catalytic Foaming agent

**Concentrate 1%, 3% & 6% Usable: 1-100% as Needed**  
**Training: 0.5%**  
**Rated: I-A (EN1568-3)**

**Approvals & Listings:**

- EN1568-3 @ 1% 3% 6& (I-A)
- (Tested @ 0.5%: 90% control fire for additional safety)
- IMO @ MPA Dresden

- ICAO-B @ 3%
- US Approvals to be completed in 2014 at UL Testing Facilities

**Fire Class Effective:** ABCDK (Intl: ABCDF)  
**Subclass Effective:** Alcohols - Esters

- Ethers • Carbon Composites
- Rubber • Plastics
- Magnesium etc.

▲ **Class A Structure Fires:**

- Total prevention of thermal inversion phenomenon
- Fast knockdown
- Great retardant reliability no re-ignition

▲ **Class B K/F-ALL Hydrocarbon Fuels (Polar, Non Polar, Fats & Vegetable Oils) Great Cooling Effect No Emulsification of Fuels**

▲ **Class C/E-Effective On: Transformer Fires; Pass Portable System "C"/E**

▲ **Class D Effective On: Magnesium, Aluminum, Titanium (Not Tested on Sodium & Lithium)**

**Wildland Fire App.**

- Air Drop • Land Based
- Structure Pretreatment

- Fire Brakes • Batch Mixable
- No Special Equipment Necessary
- Compatible with Other Products

**Additional Advantages**

- Great Temperature Reduction (1800°F to 135°F < 40 sec.)

Effective on Marine Fires (Adhere to surface such as fiberglass, etc.)

- Cold Environment Resistant: -30°F (-34.5°C)

**Storage & Handling**

- Keep in original factory sealed container or poly tanks
- Avoid contamination of product to prevent biodegradation

**Storage: -4°F to 100°F (-20°C to 37°C)**

- Do Not Store in Aluminum Container
- Do Not Mix with Hypocrite
- Do Not Use Zinc Metals, Copper or Brass Dip Tubes

**Packaging:**

- 55-gal Poly Drums (208-L) Fill wt.: 540-lbs (245-kg)
- 5-gal Carboy (20-L) Fill wt.: 49-lbs

- Bulk Packaging (By Request)
- 275-gal EU: 1000-L
- 330-gal

**Technical Specifications**

pH @ 25°C: 7.2-7.9  
 S.G. @ 25°C: 1.100-1.200

# ENVIROSAFE® EBC

## An Environment Bio-remedial Catalytic Concentrate



The EnviroSafe® Technology, is a proprietary Trade Secret Technology and formulations, within the meaning of the Uniform Trade Secret Act ("UTSA") Cal. Civ. Code Sec. 3426, Common law, Business and Profession §17200 and all other applicable statutes.

### ENVIRONMENTAL & TOXICOLOGY TESTING

FFCs' are independently tested and found to be non-hazardous to fish or any other life forms. The mixture is not an eye or skin irritant and is non-toxic when tested according to the FHSA protocols. It is judged to pose no chronic health hazard. Under European standards OECD 306, and 117 Method 2004, ISO 14669 (1999), ISO 5667-16 (1998), and ISO 10253 2006; (OSPAR/HOCNF) Part B, the FFCs meet "Green" 1 qualifying requirements. The FFCs need no special labeling or chronic health hazard warning statements and are in compliance with FHSA regulations, 16 CFR 1500 and California Proposition 65.

**LIMITED WARRANTY**  
**10-YEAR WHEN STORED WITHIN THE RECOMMENDED TEMPERATURE WHILE IN THE UNOPENED OR UNDAMAGED FACTORY SEALED ORIGINAL CONTAINER**

### DESCRIPTION

**Technology:** EnviroSafe®  
 Non flammable (FFC)  
 Bio-Remedial Technology  
 (a High Kinetic Foamer)

**Concentrate 6%**  
 • Oil Spill Remediation  
 • Decontamination

**Specification:**  
 Enviro-Safe® EBC is a water thin concentrate, fully miscible in water for premixing capacity

**Application:**  
 Ideal for systems and manual application (EBC Can Be Batch Mixed and Also Proportioned)

- Decontaminate equipment and garments
- Prevents the spread of the spill & prepares it for bio-degradation
- For onshore and offshore use

- Deployed through normal fire fighting equipment
- Spray to cover the full spill area
- Protects against ignition
- Use as needed

**Fire Class Effective:**  
 ABCDK (Intl: ABCDF)  
**Subclass Effective:**  
 Alcohols - Esters

- Ethers • Carbon Composites
- Rubber • Plastics
- Magnesium etc.

**Additional Advantages:**  
 • Effective On Marine Fires (Adheres to surface such as fiberglass, etc.)

- Cold Environment Resistant: -4°F (-20°C)
- Great Temperature Reduction (1800°F to 135°F < 40 sec.)

**Storage & Handling:**  
 • Keep in original factory sealed container or poly tanks  
 • Avoid contamination of product to prevent biodegradation

**Storage:**  
 -4°F to 90°F (-20°C to 32°C)  
 • Do not store in Aluminum container  
 • Do not mix with Hypocrite  
 • Do not use copper or brass dip tubes

**Packaging:**  
 • 55-gal Poly Drums (208-L)  
 Fill wt.: 540-lbs (245-kg)  
 • 5-gal Carboy (20-L)  
 Fill wt.: 49-lbs

• Bulk Packaging (by request)  
 275-gal EU: 1000-L  
 330-gal

**Technical Specifications**

pH @ 25°C: 7.2-7.9  
 S.G. @ 25°C: 1.100-1.200

Additional Information Available Upon Request

# ICESTOPPER™

- A General Application
- Eco-Safe
- Non-Toxic
- Non-Irritant
- Non-Aggressive Deicer



**COMING SOON**

The FFC, is a proprietary Trade Secret Technology and formulations, within the meaning of the Uniform Trade Secret Act ("UTSA") Cal. Civ. Code Sec. 3426, Common law, Business and Profession §17200 and all other applicable statutes.

## ENVIRONMENTAL & TOXICOLOGY TESTING

FFCs' are independently tested and found to be non-hazardous to fish or any other life forms. The mixture is not an eye or skin irritant and is non-toxic when tested according to the FHSa protocols. It is judged to pose no chronic health hazard. Under European standards OECD 306, and 117 Method 2004, ISO 14669 (1999), ISO 5667-16 (1998), and ISO 10253 2006; (OSPAR/HOCNF) Part B, the FFCs meet "Green" 1 qualifying requirements. The FFCs need no special labeling or chronic health hazard warning statements and are in compliance with FHSa regulations, 16 CFR 1500 and California Proposition 65.

**LIMITED WARRANTY**  
**10-YEAR WHEN STORED WITHIN THE RECOMMENDED TEMPERATURE WHILE IN THE UNOPENED OR UNDAMAGED FACTORY SEALED ORIGINAL CONTAINER**

## DESCRIPTION

Technology: FireStopper® Fire Fighting Catalyst (FFC) A High Kinetic Catalytic Foaming agent	A Clear Aqueous Water Thin Mobile Liquid, Free From Matter in Suspension
<ul style="list-style-type: none"> <li>• Stable in Storage with No Agitation Required</li> <li>• Does Not Reduce Concrete Pavement Integrity (Insignificant Surface Penetration Just Enough to Effect Cleaning)</li> </ul>	<ul style="list-style-type: none"> <li>• Long Term Resistance to Evaporation</li> <li>• Pavement Surface Cleaner: helps Remove Stains &amp; Pavement Surface Contaminates</li> </ul>
Cold Resistance: -73.4°C (-100°F)	Application: Neat Product (Use as is)
Test * Certs: This Product is in the Process and Expected to Complete in 2014	Europe: LFV Method 2-98 * 1-98, AIR5567 and Compatibility with Asphalt Concrete Pavement
Application: <ul style="list-style-type: none"> <li>• Pre-wetting: Apply at Spreader outlet at a Rate of 1.2 Gallons per 100 lbs *120 g/kg) of Solid Deicer</li> <li>• Reapply When New Accumulation Shows First Tendency to Bond</li> </ul>	Anti-icing: <ul style="list-style-type: none"> <li>• 0.5 Gallons/1000 ft2 (25 g/m2)</li> </ul> Deicing: <ul style="list-style-type: none"> <li>• 1 gallon/1000 ft2 (50 g/m2) near 32°F (0°C) on thin ice</li> <li>• 3 gallons/1000 ft2 (150 g/m2) below 10°F (-12°C) on 1 inch ice</li> </ul>
Eco-Safe This Technology is Proven to be: <ul style="list-style-type: none"> <li>• Environmentally Safe</li> <li>• Non-Toxic</li> </ul>	<ul style="list-style-type: none"> <li>• Non-Irritant</li> <li>• Non-Aggressive</li> <li>• Contains over 90% Bio-Based Component</li> </ul>
Equipment Compatibility <ul style="list-style-type: none"> <li>• Pumps: Stainless Steel (SS)</li> </ul> Positive Displacement, Centrifugal/Mechanical Seals	<ul style="list-style-type: none"> <li>• Plumbing: Stainless Steel</li> <li>• PVC • Polyethylene • Rubber</li> </ul> Avoid Galvanized Steel or Alloys with Zinc
Transfer Hoses: <ul style="list-style-type: none"> <li>• Wire Reinforced Chemical hoses (Pressure Rated Cross-Linked Polyethylene Lining &amp; EPDM Cover)</li> <li>• SS Cam &amp; Groove Fittings W/Locking Cam Levers &amp; EPDM Gaskets (Recommended)</li> </ul>	Tanks: <ul style="list-style-type: none"> <li>• SS, Fiberglass or Poly (tanks must be capable of holding high specific gravity liquid: approx. 10.4 lbs/gal [1.2 Kg/L])</li> <li>• Gaskets &amp; Seals: Butyl rubber, EPM &amp; EPDM, isoprene &amp; natural rubber, etc.</li> </ul>
Storage/Use: Do Not Use with <ul style="list-style-type: none"> <li>• Galvanized (Zinc Plated metals, Brass or Copper)</li> </ul>	<ul style="list-style-type: none"> <li>• Poor Quality Concrete</li> <li>• Other Manufacturer's Products</li> </ul>

Additional Information Available Upon Request

# FIRESTOPPER® EXP

## The World's First Eco-Safe Anti-Explosion Media & Fire Extinguishing Agent



The FFC, is a proprietary Trade Secret Technology and formulations, within the meaning of the Uniform Trade Secret Act ("UTSA") Cal. Civ. Code Sec. 3426, Common law, Business and Profession §17200 and all other applicable statutes.

### ENVIRONMENTAL & TOXICOLOGY TESTING

FFCs' are independently tested and found to be non-hazardous to fish or any other life forms. The mixture is not an eye or skin irritant and is non-toxic when tested according to the FHSa protocols. It is judged to pose no chronic health hazard. Under European standards OECD 306, and 117 Method 2004, ISO 14669 (1999), ISO 5667-16 (1998), and ISO 10253 2006; (OSPAR/HOCNF) Part B, the FFCs meet "Green" 1 qualifying requirements. The FFCs need no special labeling or chronic health hazard warning statements and are in compliance with FHSa regulations, 16 CFR 1500 and California Proposition 65.

**LIMITED WARRANTY**  
**10-YEAR WHEN STORED WITHIN THE RECOMMENDED TEMPERATURE WHILE IN THE UNOPENED OR UNDAMAGED FACTORY SEALED ORIGINAL CONTAINER**

### DESCRIPTION

**Technology:** Fire Fighting Catalyst (FFC) A High Kinetic Catalytic Foaming agent

**The "World's" First and Only Anti Explosion Liquid Agent**

**APPROVALS & LISTINGS:** Preliminary Testing Completed @ CMR Gexcon Norway

**US Approvals to be completed in 2015 at UL Testing Facilities**

**Fire Class Effective:** ABCDK (Intl: ABCDF)  
**Subclass Effective:** Alcohols - Esters

- Ethers • Carbon Composites
- Rubber • Plastics
- Magnesium • Sodium
- Lithium, etc.

**Preliminary Testing: Effective on Hydrogen & Methane**

**Additional Advantages:**

- Great Temperature Reduction (+5000°F to 135°F < 40 sec.)

**Storage & Handling:**

- Keep in original factory sealed container or poly tanks
- Avoid contamination of product to prevent biodegradation

**Storage:**

- 4°F to 90°F (-20°C to 32°C)
- Do not store in Aluminum container
- Do not use copper or brass dip tubes

**Packaging:**

- 55-gal Poly Drums (208-L) Fill wt.: 540-lbs (245-kg)
- 5-gal Carboy (20-L) Fill wt.: 49-lbs

**Bulk Packaging (by request)**

- 275-gal EU: 1000-L
- 330-gal

**Technical Specifications**

pH @ 25°C: 7.2-7.9  
 S.G. @ 25°C: 1.100-1.200

FireStopper® EXP FFC, a liquid anti explosive and fire extinguishing agent, derived from the FireStopper® FFC technology and designed to ameliorate explosive events. This liquid agent is freeze resistant to: -73.3°C (-100°F), Non-Toxic, Non-irritant and Non-Aggressive ("GREEN"). It's viscosity is water thin and will produce a light foaming event when deployed. EXP has tremendous endothermic properties that will reduce 982°C (1800°F) to ambient temperatures in less than 15-secs. In conjunction with FireStopper® Anti-Explosion Systems, this agent can suppress explosions in less than 50-ms.

Additional Information Available Upon Request

# FIRESTOPPER® MAXPROTEC™

## A Long Term Fire Retardant Designed For Pressure Treatment By The Lumber Industry And Others



The FFC, is a proprietary Trade Secret Technology and formulations, within the meaning of the Uniform Trade Secret Act ("UTSA") Cal. Civ. Code Sec. 3426, Common law, Business and Profession §17200 and all other applicable statutes.

**LIMITED WARRANTY**  
**10-YEAR WHEN STORED WITHIN THE RECOMMENDED TEMPERATURE WHILE IN THE UNOPENED OR UNDAMAGED FACTORY SEALED ORIGINAL CONTAINER**

### DESCRIPTION

**Technology:** Fire Fighting Catalyst (FFC) A High Kinetic Catalytic Low Foaming agent Water thin liquid composed of organic and inorganic compounds  
 Does not degrade the wood fiber. (Does not contain phosphorus)

MaxProtec™ is designed with exclusive properties that combine multiple fire suppression and barrier protection environments to deliver deep penetration to the fiber with tremendous endothermic capability providing short , medium and long term retardant capability

- Flame Spread Index: < 5
- Temperature Reduction: (+5000°F to 135°F < 40 sec.)
- Easy To Apply

- Non-Toxic, Non- Irritant
- Non-Hazardous
- Non-Corrosive
- Eco-Safe/Biodegradable
- No Unpleasant Odor

- Usage:**
- Vacuum Pressure treatment of construction lumber
  - Surface Pressure treatment of wooden structures

- General fire retardant as determined by enduser
- Enduser shall determine feasibility of use and application

- Suggested Evaluation:**
- ASTM E 84-87
  - ASTM D 5516-94

- ASTM D 5664-95
- ASTM E-69
- TGA/DTA

- Storage & Handling:**
- Keep in original factory sealed container or poly tanks
  - Avoid contamination of product to prevent biodegradation

- Storage:**
- 4°F to 90°F (-20°C to 32°C)
  - Do not store in Aluminum container
  - Do not use copper or brass dip tubes

- Packaging:**
- 55-gal Poly Drums (208-L) Fill wt.: 540-lbs (245-kg)
  - 5-gal Carboy (20-L) Fill wt.: 49-lbs

- Bulk Packaging (by request)
- 275-gal EU: 1000-L
- 330-gal

**Technical Specifications Available Upon Request**

pH @ 25°C: 7.2-8.4  
 S.G. @ 25°C: 1.100-1.200



# PACKAGING INFORMATION



SIZE	COLOR	APPOX. SHIPPING WT.	SHPG <sup>3</sup>
20' Container (64-Drums)	<ul style="list-style-type: none"> <li>• AB40002 FFC: Natural</li> <li>• XL FFC: Blue</li> <li>• XL "Plus" FFC: Black</li> <li>• Others: TBD</li> </ul>	<ul style="list-style-type: none"> <li>• AB40002 FFC: 14550-kg</li> <li>• XL FFC: 14630-kg</li> <li>• XL "Plus" FFC: 14660 kg</li> </ul>	N/A
275/330 gal BulkPac	Natural	TBD	49.3 ft <sup>3</sup> /57.2 ft <sup>3</sup> (1.4-m <sup>3</sup> /1.6 m <sup>3</sup> )
55 gal Drum	See Above	<ul style="list-style-type: none"> <li>• AB40002 FFC: 540-lbs (245-kg)</li> <li>• XL FFC: 554-lbs (251-kg)</li> <li>• XL "Plus" FFC: 567-lbs (257-kg)</li> <li>• Others: TBD</li> </ul>	10.9-ft <sup>3</sup> (0.3 m <sup>3</sup> )
US: 5 gal Carboy Intl: 20 Liter	<ul style="list-style-type: none"> <li>• AB40002 FFC: Blue</li> <li>• XL FFC: Natural</li> <li>• XL "Plus" FFC: Natural</li> <li>• Others: TBD</li> </ul>	<ul style="list-style-type: none"> <li>• AB40002 FFC: 49-lbs (22.2-kg)</li> <li>• XL FFC: 54-lbs (22.67-kg)</li> <li>• XL "Plus" FFC: 51.5-lbs (23.36-kg)</li> <li>• Others: TBD</li> </ul>	0.99-ft <sup>3</sup> (0.03 m <sup>3</sup> )

**IMPORTANT NOTICE TO PURCHASER:** ANY ALTERATION TO THE ORIGINAL FORMULA, EXCEPT FOR ITS INTENDED END US, SHALL VOID ANY AND ALL WARRANTIES OF PRODUCT. The following is made in lieu of all warranties, expressed or implied, including the implied warranties of merchantability and fitness for purpose: Sellers and manufacturer's only obligations shall be to replace such quantity of the product proved to be defective. Before using, user shall determine the suitability of the product for its intended use, and user will assume all risk and liability whatsoever in connection therewith. NEITHER SELLER NOT MANUFACTURER SHALL BE LIABLE IN TORT OR IN CONTRACT FOR ANY LOSS OR DAMAGE DIRECT, INCIDENTAL OR CONSEQUENTIAL, ARISING OUT OF THE USE OF OR THE INABILITY TO USE THE PRODUCT.  
**WARRANTY:** 10 YEARS WHEN STORED WITHIN THE RECOMMENDED TEMPERATURE WHILE IN THE UNDAMAGED, FACTORY SEALED, ORIGINAL CONTAINER.

FireStopper reserves the right to modify or change any or all information contained herein without prior notice.