

# MAX-SUPPRESS™ 2.6-GAL (10-LITER)

FAST RESPONSE CAC\* • MODEL: FMS-2



## FEATURES:

Stainless Steel Tank Micro Polished for Greater Corrosion Resistance

Air Cylinder (SCUBA)  
Recharge Time: 2-4 min  
Foam Discharge Distance: Approx.: 40 to 60-ft (Approx.: 12 to 18-m) depending on wind conditions

Proprietary Stainless Steel Nozzle, Variable Pattern: Straight Stream and Wide Patterns (See the liquids catalogue)

FireStopper® PFE-FR FFC Extinguishing Agent All Fire Class Effective: ABCDK (ABCDF) \*

Subclass Effective Agent:

- Alcohols • Esters • Ethers
- Carbon Composites
- Rubber • Plastics
- Lithium & Sodium Metals, etc.

Marine Alloy Aluminum Teardrop Holder

Limited Warranty: 20-year Onshore & 10-Year for Offshore Use

## SPECIFICATIONS:

Tank Capacity: 10-Liter (2.6-gal) Plumbing: Stainless Steel

1X 4-ft3 @ 3000psi (approx. 207-Bars)  
Max Discharge Rate: 90-gal/min (340-L/m)

Tank OP: >165-psi (11.37-Bars)  
Test Pressure: 600-psi (41.3-Bars)  
Burst Pressure: 2300-psi (158.5-Bars)

- Eco-Safe
- Non-Toxic
- Non-Irritant
- Non-Aggressive

Cold Environment Resistant: -100° F (-73°C)  
Operating Temperature: -59.8° F (-51° C)

Approx. Height: 23"  
Approx. Width: 13"  
Approx. Depth: 6"

Approx. Empty Weight: 15-lbs (5.44-kg)  
Charged: 35-lbs (16-kg)

\* FireStopper® PFE-FR FFC is an ECO-Safe, all fire class A-B-C-D-K (ABCDF) effective fire suppressant product exclusively available on FireStopper® Branded Products. Additionally, this product is Non-Toxic, Non-Irritant, Non-Aggressive, and approved for use on off shore and onshore applications. Tested and rated under UL711, ULC, NFPA10, EN3-7