

MAX-SUPPRESS™ 30-GAL (114-L) FAST RESPONSE CAC • MODEL: FMS-30-S



FEATURES:

Stainless Steel Tank Micro Polished for Greater Corrosion Resistance
Stainless Plumbing

FireStopper® PFE-FR FFC Extinguishing Agent All Fire Class Effective: ABCDK (ABCDF)

Subclass Effective Agent:

- Alcohols • Esters • Ethers
- Carbon Composites
- Rubber • Plastics • Lithium & Sodium Metals, etc.

Air Cylinder (SCUBA)
Regulator Adjustable Pressure: 0-400-psi (0-27-Bars)
Stainless Steel Pressure Gauge

Multiple Foam Expansion Capability: Low Med + Variable
Operating Pressure Capability

Discharge Nozzle:
1" FireStopper®/Akron SaberJet Tri Spay Pistol Grip

Dispensing Hose: UL Listed Hard Rubber or Collapsible

Powder Coated All Steel Frame for Long Term Protection

Limited Warranty:
20-year Onshore & 10-Year for Offshore Use

OPTIONS & ACCESSORIES

Hose with Reel

Protective Cover

SPECIFICATIONS:

Capacity: 30-gal (113.5-L)
Max OP: >350-psi (24-Bar)
Test Pressure: 600-psi (41.4-Bars)
Burst Pressure: 1200-psi (82.7-Bars)

- Eco-Safe
- Non-Toxic
- Non-Irritant
- Non-Aggressive

Cold Environment Resistant:
-30° to -100° F (-34.5° to -73.3°C)
Operating Temp: -40°F (-40°C)
Operating Pressure: >160-psi (11-Bar)

2X 58-ft³ (2.36-m³) @ 3000psi (approx. 207-Bars)
Max Discharge Rate:
300-gal/min (1136-L/m)

Foam Expansion Vol.:
Low: 10X 300-gal (1136-liters)
Med: 20X 600-gal (2272-liters)

Foam Discharge Distance:
Approx.: 65 to 75-ft (20 to 23-m)
Subject to wind Conditions

Hose Size: 1" (25.4-mm)
Hose Length: 50-ft (15-m)

Approx. Measurement:
Height: 35"
Width: 31"
Length: 55.5"

Approx. Empty Weight:
360-lbs (163-kg) Charged:
684-lbs (310-kg)

Available in Hazmat Configuration

500-ft (152.4-m)

Fitted Durable Canvas